



# RING Honeycomb matting

16/07/2014

## STANDARD MATTING

### FEATURES

- Honeycomb design.
- Non-slip surface.
- Open or closed.

### ADVANTAGES

- Non-slippery
- Thermal and acoustic insulation
- Noise, vibration, and cold propagation reduction
- High damping and insulation power
- Reduces tiredness and helps to increase productivity
- Mud-removing
- Easy to take up and clean
- Suitable to be used with wet and cold floors

### BENEFITS

- Safety
- Comfort
- Performance
- Economy
- Cleanliness

### APPLICATIONS

Heavy transit areas.

Floor mats at work stations.

The open variety has been developed for self-draining, and is especially appropriate for swimming pools, health resorts, beach areas, or any place where drainage is required.

[www.trelleborg.com/elastomerlaminates](http://www.trelleborg.com/elastomerlaminates)


## MECHANICAL, PHYSICAL AND CHEMICAL PROPERTIES

	Measured characteristics	Standard	Value	
<b>MECHANICAL</b>				
	Rubber compound		SBR	
	Hardness	ASTM D2240	70 ± 5	Shore A
	Abrasion resistance (5 N)	ISO 4649	≤ 250	mm <sup>3</sup>

PROFILE	PATTERN
---------	---------



Honeycomb (MH) open



Honeycomb (MH) closed

## DIMENSIONS

Colour	Thickness (mm)		Width (mm)		Length (m)		Weight (kg/m <sup>2</sup> )	Pattern
●	14	± 1	1000	± 2 %	1.8	± 2 %	8	MH open
●	22	± 1.75	800	± 2 %	1.2	± 2 %	15	MH open
●	22	± 1.75	1000	± 2 %	1.5	± 2 %	15	MH open
●	14	± 1	1000	± 2 %	1.8	± 2 %	9.5	MH closed

## IDENTIFICATION

Branding	Without.
Back face	With support pivot pins.
Packaging	Laid onto the pallet.
Wrapping	Black polyethylene film.
Labelling	Self-adhesive label indicating product name, dimensions, area in m <sup>2</sup> , nominal weight, and product code to allow product traceability.