

BIOVAST RED



PROCESSING EQUIPMENT

Food industry
Cleaning



APPLICATIONS

For cleaning and wash-down operations in food industry.

Also suitable for transfer of aqueous, acidic, alcoholic or fatty liquid foodstuffs.

ADVANTAGES

- ┆ Can be used in any food industry environments (dairies, slaughterhouses, etc.).
- ┆ Highly flexible.
- ┆ Non staining cover.
- ┆ Contains no phthalate.

TECHNICAL DESCRIPTION

Inner tube: food grade quality oil resistant NBR, white, smooth.

Reinforcement: synthetic textile.

Cover: oil and weather resistant NBR/PVC, red, smooth.

Temperature range:

Water: -20 °C to +100 °C/WP=20bar.

Steam: +165 °C/6bar.

STANDARD/APPROVAL

EU regulations No. 1935/2004, 2023/2006.



FDA regulation No. 21 CFR 177.2600.




French legislation.



All relevant migrations tests (France and FDA) were performed by the French institute of Poitiers (IANESCO) and confirmed compliant.

COUPLINGS/FITTINGS

Specially designed fittings are available, please contact us for further information in order to get optimum connections.



**PROCESSING EQUIPMENT****BIOVAST RED**

ID mm	OD mm	WORKING PRESSURE (STEAM) bar	WORKING PRESSURE (WATER) bar	BURSTING PRESSURE bar	BENDING RADIUS mm	WEIGHT kg/m	LENGTH m	ARTICLE NUMBER	STOCK () or min. order m
13.0 ±0.8	23.0 ±0.9	6	20	60	65	0.36	20	5513767	1
13.0 ±0.8	23.0 ±0.9	6	20	60	65	0.36	40	5513768	1
13.0 ±0.8	23.0 ±0.9	6	20	60	65	0.36	60	5513769	1
16.0 ±1.0	26.0 ±1.0	6	20	60	85	0.43	20	5513770	1
16.0 ±1.0	26.0 ±1.0	6	20	60	85	0.43	40	5513771	1
19.0 ±1.0	31.0 ±1.0	6	20	60	100	0.59	20	5513772	1
19.0 ±1.0	31.0 ±1.0	6	20	60	100	0.59	40	5513773	1
25.0 ±1.0	37.0 ±1.0	6	20	60	125	0.69	20	5513774	1
25.0 ±1.0	37.0 ±1.0	6	20	60	125	0.69	40	5513775	1

Tolerance on length: ±1% (ISO 1307 Standard).

