

TRELLJET 681 AP



PROCESSING EQUIPMENT

Food industry
High pressure jetting



APPLICATIONS

Specially designed for professional and industrial high pressure cleaning.

The antimicrobial TRELLEJET 681 is suitable for all environments where bacteria are concerned: cleaning companies, food industries, pharmaceuticals, packaging/bottling, health care institutions, schools, etc.

Suitable for mobile pressure washers, fixed installations and reel mounted applications.

ADVANTAGES

- ┆ Crush resistant.
- ┆ Antimicrobial protection: prevents odor, stain, degradation and breakdown from bacterial attacks.
- ┆ Non-staining smooth cover.
- ┆ Oil, detergents, wear and weather resistant.
- ┆ High temperature resistance.
- ┆ Highly flexible and kink resistance.
- ┆ Long service life.

TECHNICAL DESCRIPTION

Inner tube: NBR/SBR, black, smooth.

Reinforcement: synthetic textile.

Cover: NBR/SBR, blue, smooth.

Temperature range: -40°C to +120°C.

Special properties: Antimicrobial protection in reference to:
- ISO 22196:2007 (Quantitative analysis of bacterial growth).
- AATCC 30-2004 (Qualitative analysis to evaluate the antimicrobial activity of fungicides).

COUPLINGS/FITTINGS

Specially designed fittings are available, please contact us for further information in order to get optimum connections.

COMPLEMENTARY INFORMATION

Available in random lengths: 20-95m.
50% of the volume in each delivery will be random lengths, shortest length of 20m, at least 50% will be in fixed length mentioned in the table.

ND 10mm



TRELLEBORG



TRELLJET 681



Antimicrobial protection ND 13 - 1/2" - WP 200 BAR / 2900 PSI - MAX 120°C - Made in France



**PROCESSING EQUIPMENT****TRELLJET 681 AP**

ID mm	WALL THICKNESS mm	OD mm	REINF. DIAMETER mm	WORKING PRESSURE bar	BURSTING PRESSURE bar	BENDING RADIUS mm	WEIGHT kg/m	MAX. LENGTH m	ARTICLE NUMBER	STOCK () or min. order m
9.5 +0.6 -0.2	4.5	18.5 ±0.8	15 ±0.3	200	500	60	0.29	95	5603263	⌘
9.5 +0.6/-0.2	4.5	18.5 ±0.8	15 ±0.3	200	500	60	0.29	100	5603183	⌘
12.7 ^{+0.8} _{0.4} -	4.5	21.7 ±0.6	18.3 ±0.3	200	500	70	0.4	95	5603264	⌘
12.7 +0.8/-0.4	4.5	21.7 ±0.8	18 ±0.3	200	500	70	0.4	100	5603184	⌘

Tolerance on length: ±1% (ISO 1307 Standard).

⌘ Upon availability.

Digital version

WWW.TRELLEBORG.COM/FLUIDHANDLING