

# TRELLOIL D EC



## OIL & GAS

Oil and petroleum  
Oil cargo



### APPLICATIONS

Transfer of petroleum products with aromatic content up to 50% in large diameters.

### ADVANTAGES

- † Highly robust and flexible.
- † Cover particularly resistant to hydrocarbons, abrasion, atmospheric conditions and ozone.
- † Electrical conductivity fully assured by the inner tube compound.

### TECHNICAL DESCRIPTION

Inner tube: oil and petrol resistant NBR, black, smooth.

Reinforcement: synthetic textile.

Cover: oil and weather resistant CR, black, fabric impression.

Temperature range: -40°C to +100°C.

Electrical properties: conductive tube,  $R < 10^6 \Omega / \text{lg}$ .

### COMPLEMENTARY INFORMATION

Can be delivered with swaged fittings: steel flange PN20 or larger, Victaulic, male or female threaded fittings.  
Please consult us for any other type of ends or delivery lengths.



**OIL & GAS****TRELLOIL D EC**

ID mm	WALL THICKNESS mm	OD mm	WORKING PRESSURE bar	BURSTING PRESSURE bar	BENDING RADIUS mm	WEIGHT kg/m	LENGTH m	ARTICLE NUMBER	STOCK ( ) or min. order m
100.0 ±1.5	9 ±0.8	118.0 ±1.5	20	60	600	4.08	1	5513112	40
125.0 ±1.5	9 ±0.8	143.0 ±1.5	20	60	750	5.04	1	5513113	40
150.0 ±1.5	10 ±0.8	170.0 ±1.5	20	60	900	6.5	1	5513114	40
204.0 ±1.5	11 ±1.0	226.0 ±1.5	20	60	1400	9.81	1	5513115	40
251.0 ±2.0	11 ±1.25	273.0 ±2.0	20	60	1800	11.67	1	5513116	40

Tolerance on length: ±1% (ISO 1307 Standard).

Digital version



[WWW.TRELLEBORG.COM/FLUIDHANDLING](http://WWW.TRELLEBORG.COM/FLUIDHANDLING)