

# MULTI 15



**MANUFACTURING &  
MACHINE TOOLS**



Air and water

## APPLICATIONS

Compressed air and water hose in industrial applications.

## TECHNICAL DESCRIPTION

Inner tube: SBR, black, smooth.

Reinforcement: synthetic textile.

Cover: SBR, black, smooth.

Temperature range: -30°C to +70°C.

6-25mm



32-63mm





| ID<br>mm | OD<br>mm | WORKING<br>PRESSURE<br>bar | BURSTING<br>PRESSURE<br>bar | BENDING<br>RADIUS<br>mm | WEIGHT<br>kg/m | LENGTH<br>m | ARTICLE<br>NUMBER | STOCK ( ) or<br>min. order<br>m |
|----------|----------|----------------------------|-----------------------------|-------------------------|----------------|-------------|-------------------|---------------------------------|
| 6.0      | 12.0     | 15                         | 45                          | 30                      | 0.13           | 40          | 5513820           |                                 |
| 8.0      | 14.0     | 15                         | 45                          | 40                      | 0.16           | 40          | 5513821           |                                 |
| 10.0     | 16.0     | 15                         | 45                          | 50                      | 0.19           | 40          | 5513822           |                                 |
| 13.0     | 20.0     | 15                         | 45                          | 65                      | 0.29           | 40          | 5513823           |                                 |
| 16.0     | 23.0     | 15                         | 45                          | 80                      | 0.34           | 40          | 5513824           |                                 |
| 19.0     | 26.0     | 15                         | 45                          | 90                      | 0.39           | 40          | 5513825           |                                 |
| 25.0     | 33.0     | 15                         | 45                          | 110                     | 0.57           | 40          | 5513826           |                                 |
| 32.0     | 42.0     | 15                         | 45                          | 320                     | 0.77           | 40          | 5513827           |                                 |
| 38.0     | 48.0     | 15                         | 45                          | 380                     | 0.89           | 40          | 5513828           |                                 |
| 51.0     | 63.0     | 15                         | 45                          | 510                     | 1.43           | 40          | 5513829           |                                 |
| 63.0     | 77.0     | 15                         | 45                          | 630                     | 2              | 40          | 5513830           |                                 |

Tolerance on length:  $\pm 1\%$  (ISO 1307 Standard).



TRELLEBORG