

# PROJECTOR 40



## BUILDINGS & CONSTRUCTION

Spraying



### APPLICATIONS

For spraying of mortar and mixed concrete as well as dry products.

Used as a service hose between pump and nozzle in transporting plaster, grout and ready mixed concrete.

### ADVANTAGES

- Light weight, flexible and is easy to handle.
- Abrasion resistant tube compound.
- Conductive inner tube compound gives increased safety for the operator.
- Non-staining white cover avoids traces on walls and floors.

### TECHNICAL DESCRIPTION

Inner tube: wear resistant NR, black, smooth.

Reinforcement: synthetic textile.

Cover: wear and weather resistant SBR, black, fabric impression.

Temperature range: -30 °C to +70 °C.


Electrical properties: conductive tube,  $R < 2 \cdot 10^6 \Omega/m$ .

Special properties: abrasion resistance of tube  $< 40 \text{ mm}^3$  according to ISO 4649.



TRELLEBORG

**PROJECTOR 40** WP 12 BAR



**BUILDINGS & CONSTRUCTION****PROJECTOR 40**

ID mm	WALL THICKNESS mm	OD mm	WORKING PRESSURE bar	BURSTING PRESSURE bar	BENDING RADIUS mm	WEIGHT kg/m	LENGTH m	ARTICLE NUMBER	STOCK ( ) or min. order m
25.0	9.5 ±0.50	44.0 ±1.0	12	40	120	1.2	40	59006811	1
32.0	10 ±0.50	52.0 ±1.0	12	40	150	1.57	40	59006812	1
40.0	10 ±0.50	60.0 ±1.0	12	40	180	1.8	20	59006813	1
40.0	10 ±0.50	60.0 ±1.0	12	40	180	1.8	40	59006814	1
50.0	10 ±0.75	70.0 ±1.5	12	40	250	2.22	20	59006815	1
50.0	10 ±0.75	70.0 ±1.5	12	40	250	2.22	40	59006816	1
60.0	10 ±0.75	80.0 ±1.5	12	40	290	2.3	20	59006817	1
60.0	10 ±0.75	80.0 ±1.5	12	40	290	2.3	40	59006818	1
63.0	13.5 ±0.75	90.0 ±1.5	12	40	340	2.83	20	59006949	1
65.0	10 ±0.75	85.0 ±1.5	12	40	320	2.7	20	59006819	1
65.0	10 ±0.75	85.0 ±1.5	12	40	320	2.7	40	59006820	1

Tolerance on length: ±1% (ISO 1307 Standard).

Digital version

[WWW.TRELLEBORG.COM/FLUIDHANDLING](http://WWW.TRELLEBORG.COM/FLUIDHANDLING)