

PULSOR 170 L-WHIP



BUILDINGS & CONSTRUCTION

Concrete pump and placement



APPLICATIONS

High pressure concrete pump hose for boom transfer, placement.

ADVANTAGES

- ┌ Prevents whipping effects when air is compressed in the delivery system, then released.
- ┌ Avoids risks of injuries.
- ┌ Highly abrasion resistant hose to give extended service life.

TECHNICAL DESCRIPTION

Inner tube: abrasion resistant NR/SBR, black, smooth.

Reinforcement: 4 steel cords plies and specific reinforcement.

Cover: abrasion and weather resistant NR/SBR, black, fabric impression.

Temperature range: -30°C to +80°C.

COUPLINGS/FITTINGS

Hose assembly delivered with one crimped coupling according to VICTAULIC or concrete pump manufacturers (PUTZMEISTER, SCHWING, etc.) dimensions.

COMPLEMENTARY INFORMATION

Regular safety rule should be observed and the area around hose end should be evacuated during cleaning operation whenever pumping deviation occurs indicating air in the boom.



**BUILDINGS & CONSTRUCTION****PULSOR 170 L-WHIP**

| ID mm | WALL THICKNESS mm | OD mm | WORKING PRESSURE bar | BURSTING PRESSURE bar | MAX. VACUUM bar | WEIGHT kg/m | LENGTH m | ARTICLE NUMBER | STOCK () or min. order m |
|----------|-------------------------|------------|----------------------------|-----------------------------|-----------------------|----------------|-------------|-------------------|---------------------------------|
| 102.0 | 13 ±1.0 | 129.0 ±2.0 | 85 | 170 | 0.8 | 7.93 | 1 | 5603103 | 1 |
| 125.0 | 14 ±1.0 | 154.0 ±2.0 | 85 | 170 | 0.8 | 10.25 | 1 | 5603247 | 1 |

Tolerance on length: ±1% (ISO 1307 Standard).

**TRELLEBORG**

WWW.TRELLEBORG.COM/FLUIDHANDLING