SOLVYKLER

MANUFACTURING & MACHINE TOOLS

Hot water and multipurpose chemicals

APPLICATIONS

Pressure service line for ester, ketone, alcohol based paints and numerous chemicals.

ADVANTAGES

- Hose cover resistant to splashing of corrosive chemicals.
- Free from silicone.
- Hose remains flexible within a wide temperature range.
- Antistatic tube.

TECHNICAL DESCRIPTION

Inner tube: chemical resistant EPDM, black, smooth.
Reinforcement: synthetic textile.
Cover: chemical and weather resistant EPDM, green, smooth.
Temperature range: -30°C to +100°C.
Electrical properties: antistatic tube, $R<10^6\Omega/m$.

COUPLINGS/FITTINGS

Special paint hose couplings are recommended.



SOLVYKLER

ID mm	WALL THICKNESS mm	OD mm	WORKING PRESSURE bar	BURSTING PRESSURE bar	BENDING RADIUS mm	WEIGHT kg/m	LENGTH m	ARTICLE NUMBER	STOCK (l) or min. order m
6.0 ±0.4	3.3	12.6 ±0.5	20	60	60	0.13	20	0060304	¤
6.0 ±0.4	3.3	12.6 ±0.5	20	60	60	0.13	40	0060305	l
6.0 ±0.4	3.3	12.6 ±0.5	20	60	60	0.13	80	0060306	3200
6.0 ±0.4	3.3	12.6 ±0.5	20	60	60	0.13	120	0060307	3240
8.0 ±0.5	3.5	15.0 ±0.6	20	60	70	0.16	20	0060308	¤
8.0 ±0.5	3.5	15.0 ±0.6	20	60	70	0.16	40	0060309	l
8.0 ±0.5	3.5	15.0 ±0.6	20	60	70	0.16	80	0060310	3280
8.0 ±0.5	3.5	15.0 ±0.6	20	60	70	0.16	120	0060311	3240
9.0 ±0.5	3.5	16.0 ±0.6	20	60	85	0.17	20	0060281	¤
9.0 ±0.5	3.5	16.0 ±0.6	20	60	85	0.17	40	0060282	l
9.0 ±0.5	3.5	16.0 ±0.6	20	60	85	0.17	80	0060283	3280
9.0 ±0.5	3.5	16.0 ±0.6	20	60	85	0.17	120	0060285	3240
10.0 ±0.5	4	18.0 ±0.6	20	60	90	0.22	20	0060312	¤
10.0 ±0.5	4	18.0 ±0.6	20	60	90	0.22	40	0060313	l
10.0 ±0.5	4	18.0 ±0.6	20	60	90	0.22	80	0060314	3280
10.0 ±0.5	4	18.0 ±0.6	20	60	90	0.22	120	0060315	3240
13.0 ±0.6	4	21.0 ±0.7	20	60	110	0.27	20	0060718	¤
13.0 ±0.6	4	21.0 ±0.7	20	60	110	0.27	40	0060719	l
13.0 ±0.6	4	21.0 ±0.7	20	60	110	0.27	80	0060720	2400
13.0 ±0.6	4	21.0 ±0.7	20	60	110	0.27	120	0060721	l
16.0 ±0.8	4	24.0 ±1.0	20	60	130	0.32	20	0070139	1200
16.0 ±0.8	4	24.0 ±1.0	20	60	130	0.32	40	0070140	1200
16.0 ±0.8	4	24.0 ±1.0	20	60	130	0.32	80	0070141	1200
20.0 ±0.8	4.5	29.0 ±1.0	20	60	150	0.44	20	0070142	¤
20.0 ±0.8	4.5	29.0 ±1.0	20	60	150	0.44	40	0070143	l
20.0 ±0.8	4.5	29.0 ±1.0	20	60	150	0.44	80	0070144	l
25.0 ±1.2	4.5	34.0 ±1.5	20	60	170	0.54	20	0070145	¤
25.0 ±1.2	4.5	34.0 ±1.5	20	60	170	0.54	40	0070146	l
25.0 ±1.2	4.5	34.0 ±1.5	20	60	170	0.54	80	0070147	800

Tolerance on length: ±1% (ISO 1307 Standard). ¤ Upon availability.

Digital version

TRELLEBORG

WWW.TRELLEBORG.COM/FLUIDHANDLING