

# STEAM 16 RED



OIL & GAS

Steam



## APPLICATIONS

High pressure steam hose.

## TECHNICAL DESCRIPTION

Inner tube: synthetic EPDM rubber, black, smooth.

Reinforcement: steel braid.

Cover: synthetic EPDM rubber, red, fabric impression.

Temperature range: -30°C to +210°C.

Electrical properties:  $R < 1M\Omega/lg$ .

## STANDARD/APPROVAL

BS5342:1985 type 2 class A.



13-25mm:



32-51mm:



**OIL & GAS****STEAM 16 RED**

ID mm	OD mm	WORKING PRESSURE bar	BURSTING PRESSURE bar	BENDING RADIUS mm	WEIGHT kg/m	LENGTH m	ARTICLE NUMBER	STOCK ( ) or min. order m
13.0 ±0.75	24.0 ±1	16	160	150	0.51	40	5513659	1
16.0 ±0.75	28.0 ±1	16	160	190	0.64	40	5513660	840
19.0 ±0.75	32.0 ±1	16	160	230	0.8	40	5513661	1
19.0 ±0.75	32.0 ±1	16	160	230	0.8	60	5514008	2400
25.0 ±0.75	38.0 ±1	16	160	300	1	40	5513662	1
25.0 ±0.75	38.0 ±1	16	160	300	1	60	5514009	720
32.0 ±0.75	48.0 ±1	16	160	320	1.44	40	5513663	600
38.0 ±0.75	54.0 ±1.2	16	160	380	1.75	40	5513664	600
51.0 ±0.75	69.0 ±1.4	16	160	500	2.31	40	5513665	1

Tolerance on length: ±1% (ISO 1307 Standard).

**TRELLEBORG**