

# AQUA 10 SD

 **AGRICULTURE**

Water  
Suction applications



## APPLICATIONS

Water suction and delivery hose used for industrial water, waste water and agricultural equipment.


## TECHNICAL DESCRIPTION

Inner tube: SBR, black, smooth.

Reinforcement: synthetic textile with embedded steel helix.

Cover: SBR, black, fabric impression.

Temperature range: -30°C to +80°C.



**AGRICULTURE****AQUA 10 SD**

ID mm	OD mm	WORKING PRESSURE bar	BURSTING PRESSURE bar	MAX. VACUUM bar	BENDING RADIUS mm	WEIGHT kg/m	LENGTH m	ARTICLE NUMBER	STOCK ( ) or min. order m
25.0	35.0 ±1	10	30	0.9	100	0.71	40	5503700	∞
32.0	42.0 ±1	10	30	0.9	120	1.01	40	5503701	∞
38.0	48.0 ±1	10	30	0.9	160	1.19	40	5503702	∞
51.0	63.0 ±1	10	30	0.9	200	1.72	40	5503703	∞
63.0	75.0 ±1	10	30	0.9	245	2.23	20	59007854	∞
63.0	75.0 ±1	10	30	0.9	245	2.23	40	5503704	160
76.0	88.0 ±1	10	30	0.9	320	2.57	20	59007855	∞
76.0	88.0 ±1	10	30	0.9	320	2.57	40	5503705	160
90.0	103.0 ±1.2	10	30	0.9	360	3.36	20	59007856	∞
90.0	103.0 ±1.2	10	30	0.9	360	3.36	40	5503706	160
102.0	116.0 ±1.2	10	30	0.9	410	4.05	20	59007857	∞
102.0	116.0 ±1.2	10	30	0.9	410	4.05	40	5503695	∞
127.0	143.0 ±1.2	10	30	0.9	510	5.82	20	59007858	∞
127.0	143.0 ±1.2	10	30	0.9	510	5.82	40	5503696	∞
152.0	169.0 ±1.2	10	30	0.9	610	7.66	20	59007859	∞
152.0	169.0 ±1.2	10	30	0.9	610	7.66	40	5503697	∞
203.0	225.0 ±1.6	10	30	0.8	1000	13.28	20	59007860	∞
203.0	225.0 ±1.6	10	30	0.8	1000	13.28	40	5503698	∞
254.0	276.0 ±1.6	10	30	0.8	1270	19.17	20	59007861	∞
254.0	276.0 ±1.6	10	30	0.8	1270	19.17	40	5503699	∞

Tolerance on length: ±1% (ISO 1307 Standard).

**TRELLEBORG**[WWW.TRELLEBORG.COM/FLUIDHANDLING](http://WWW.TRELLEBORG.COM/FLUIDHANDLING)