

TRELLBLAST S



**BUILDINGS &
CONSTRUCTION**

Blasting and guniting



APPLICATIONS

For cleaning and shot blasting castings, metal, stone and concrete surfaces.

ADVANTAGES

- ┆ Light weight and flexible for easy handling.
- ┆ Conductive inner tube compound gives increased safety for the operator, since there is no risk of wire breakage in use.

TECHNICAL DESCRIPTION

Inner tube: wear resistant NR, black, smooth.


Reinforcement: synthetic textile.

Cover: wear and weather resistant SBR, black, fabric impression.

Temperature range: -30 °C to +70 °C.

Electrical properties: conductive tube, $R < 2 \cdot 10^6 \Omega/m$.

Special properties: abrasion resistance of tube $< 70 \text{mm}^3$ according to ISO 4649.





ID mm	WALL THICKNESS mm	OD mm	WORKING PRESSURE bar	BURSTING PRESSURE bar	BENDING RADIUS mm	WEIGHT kg/m	LENGTH m	ARTICLE NUMBER	STOCK () or min. order m
13.0	7 ±0.5	27.0 ±1	10	30	65	0.56	40	5026067	1
25.0	7 ±0.5	39.0 ±1	10	30	125	0.86	40	5501322	1
32.0	8 ±0.5	48.0 ±1	10	30	160	1.3	40	5501323	1

Tolerance on length: ±1% (ISO 1307 Standard).

Digital version



TRELLEBORG