

TRELLVAC Extractor HD



CONSTRUCTION & MINING EQUIPMENT

Evacuation and material handling
hoses



APPLICATIONS

Universal material handling hose for suction of shavings, sand, dust and powder, etc.

Applications include sawmills, chip board and wood veneer plants, fiberboard plants, etc.

ADVANTAGES

- ┆ Light and flexible design with steel helix.
- ┆ Good bending radius.
- ┆ Especially useful when low weight and easy handling in combination with good abrasion resistance are valued.

TECHNICAL DESCRIPTION

Inner tube: wear resistant SBR/NR, black, smooth.

Reinforcement: synthetic textile with embedded steel helix.

Cover: wear and weather resistant SBR/NR, black, corrugated.

Temperature range: -40°C to +90°C.

Electrical properties: conductive tube and cover, $R < 10^6 \Omega/m$.



COMPLEMENTARY INFORMATION

OD measured on top of corrugation.





**CONSTRUCTION & MINING
EQUIPMENT**

TRELLVAC Extractor HD



ID mm	OD mm	MAX. VACUUM bar	BENDING RADIUS mm	WEIGHT kg/m	LENGTH m	ARTICLE NUMBER	STOCK () or min. order m
38.0	47.0 ±1.5	0.9	50	0.73	12	0124823	
51.0	60.0 ±1.5	0.9	75	0.96	12	0129711	
63.0	72.0 ±1.5	0.9	100	1.13	12	0124849	
76.0	85.0 ±1.5	0.9	120	1.37	12	0124825	
102.0	111.0 ±1.5	0.9	150	1.85	12	0125779	
127.0	136.0 ±1.5	0.7	175	2.33	12	0124828	
152.0	161.0 ±1.5	0.4	200	2.77	12	0124829	

Tolerance on length: ±1% (ISO 1307 Standard).

Digital version



TRELLEBORG

WWW.TRELLEBORG.COM/FLUIDHANDLING