

TRELLVAC Extractor LD



CONSTRUCTION & MINING EQUIPMENT

Evacuation and material handling
hoses



APPLICATIONS

Universal ducting hose for dust, wood chips, small particles and various types of gas.

ADVANTAGES

- Light and flexible.
- Excellent bending radius.
- Especially useful when low weight and easy handling are valued.

TECHNICAL DESCRIPTION

Inner tube: wear resistant SBR/NR, black, smooth.

Reinforcement: synthetic textile with embedded steel helix.

Cover: wear and weather resistant SBR/NR, black, corrugated.

Temperature range: -40 °C to +90 °C.

Electrical properties: conductive tube and cover,
 $R < 10^6 \Omega/m$.



COMPLEMENTARY INFORMATION

OD measured on top of corrugation.





ID mm	OD mm	MAX. VACUUM bar	BENDING RADIUS mm	WEIGHT kg/m	LENGTH m	ARTICLE NUMBER	STOCK () or min. order m
38.0	44.5 ±1.0	0.9	45	0.62	12	0025890	
51.0	57.5 ±1.0	0.9	70	0.81	12	0025908	
63.0	70.0 ±1.0	0.9	95	0.87	12	0025916	
76.0	83.5 ±1.0	0.9	115	1.04	12	0025932	
90.0	97.5 ±1.0	0.9	125	1.22	12	0025965	
102.0	110.5 ±1.0	0.9	145	1.57	12	0025973	
113.0	121.5 ±1.5	0.9	155	1.73	12	0025981	
127.0	135.5 ±1.5	0.7	170	1.93	12	0026005	
152.0	160.5 ±1.5	0.4	195	2.3	12	0026013	
178.0	186.5 ±1.5	0.25	220	2.68	12	0026021	12
204.0	212.5 ±1.5	0.15	245	3.06	12	0026039	

Tolerance on length: ±1% (ISO 1307 Standard).

Digital version



TRELLEBORG